

## AutoPrinter Specifications

For specifications on the Everest II or PrismPlus! printer, please see the printer section.

Printer throughput specifications will always have a few disclaimers. Here's ours :

1. Printer throughput is dependent on the size of the files you are trying to print. If the files are so large that the driving computer can not get them processed as fast as the printer will print then file or image processing becomes the bottleneck and the printer throughput will not match the numbers below.
2. If the driving computer is slow, or overburdened, or lacks sufficient free disc space then even if the files to be printed are not overly large, the computer will not be able to process and ship the files as fast as the printer can print them and the throughput will not match the numbers below.

<b>AutoEverest II Throughput *</b>	Normal mode - 60 per hour
	Best mode - 46 per hour
<b>AutoPrismPlus! Throughput</b>	300 x 300 dpi - full coverage - 167 half coverage - 240
	300 x 600 dpi - full coverage - 164 half coverage - 240
<b>System Requirements</b>	Pentium or greater with minimum 64MB RAM Windows XP requires 128MB RAM
<b>Interface</b>	Prism - Parallel for printer, serial included for firmware updates
	Everest II - USB for printer, serial included for firmware updates
<b>Power</b>	100 - 240 VAC, 4.7 A/3.7 A, 60/50 Hz
<b>Operating Temperature</b>	60° F to 86°F (15.5°C to 30°C)
<b>Relative Humidity</b>	30% to 80% non-condensing
<b>Certifications</b>	Emissions: FCC Class B, EN 55022 Class B
	Susceptibility: EN55024 Safety: EN 60950, UL1950, c-UL1950
	Conformance Marks: UL, cUL, CE
<b>Physical</b>	Height 22" Width 15.1" Depth 21.2"
<b>(Includes carousel but not printer)</b>	(55.9 cm x 38.4 cm x 53.8 cm)
	Weight 35.8 lbs (16.2 kg)
<b>Warranty</b>	One year limited depot
<b>Service Options</b>	Various Rimage Service Programs are available. Contact your local Rimage Service Representative for details.